

Class 150 RTJ

Diameter (inches)	A	B	C	K	E	F	G	Unit weight spade Kg	Unit weight spacer Kg
1/2"	-	-	-	-	-	-	-	-	-
3/4"	-	-	-	-	-	-	-	-	-
1"	64	32	16	100	47.6	8.7	6.4	0.5	0.3
1.1/2"	83	48	16	100	65.1	8.7	6.4	0.7	0.5
2"	102	60	18	100	82.6	8.7	6.4	1.1	0.7
2.1/2"	-	-	-	-	-	-	-	-	-
3"	134	89	20	135	114.3	8.7	6.4	2.3	1.4
4"	172	114	22	135	149.2	8.7	6.4	4.1	2.4
6"	219	168	24	135	193.7	8.7	6.4	7.3	3.2
8"	273	219	28	135	247.7	8.7	6.4	12.5	4.6
10"	330	273	30	135	304.8	8.7	6.4	20.5	8.6
12"	407	324	36	135	381	8.7	6.4	36	14
14"	426	356	36	160	396.9	8.7	6.4	40	15.5
16"	483	406	40	160	454	8.7	6.4	57.5	17
18"	546	457	44	160	517.5	8.7	6.4	79.5	24
20"	597	508	44	160	558.8	8.7	6.4	98.5	28
24"	711	610	52	200	673.1	8.7	6.4	160	43.5

Class 300 RTJ

Diameter (inches)	A	B	C	K	E	F	G	Unit weight spade Kg	Unit weight spacer Kg
1/2"	51	19	18	150	34.1	7.1	5.6	0.5	0.5
3/4"	64	25	20	160	42.9	8.7	6.4	0.7	0.7
1"	70	32	21	160	50.8	8.7	6.4	0.8	0.7
1.1/2"	91	48	24	160	68.3	8.7	6.4	1.5	1.1
2"	108	60	27	160	82.6	11.9	7.9	2.2	1.6
2.1/2"	127	73	26	160	-	-	-	2.8	1.8
3"	146	89	27	160	123.8	11.9	7.9	3.8	2.5
4"	175	114	29	165	149.2	11.9	7.9	5.7	3.4
6"	241	168	34	165	211.1	11.9	7.9	13	6.5
8"	302	219	38	165	269.9	11.9	7.9	23	12
10"	356	273	42	170	323.9	11.9	7.9	34	15
12"	413	324	47	180	381	11.9	7.9	51	21
14"	457	356	50	185	419.1	11.9	7.9	66	27
16"	508	406	54	185	469.9	11.9	7.9	88	33
18"	575	457	58	190	533.4	11.9	7.9	120	45
20"	635	508	65	190	584.2	13.5	9.5	163	60
24"	749	610	77	200	692.2	16.7	11.1	268	92

Class 600 RTJ

Diameter (inches)	A	B	C	K	E	F	G	Unit weight spade Kg	Unit weight spacer Kg
1/2"	51	19	18	150	34.1	7.1	5.6	0.5	0.5
3/4"	64	25	20	160	42.9	8.7	6.4	0.7	0.7
1"	70	32	21	160	50.8	8.7	6.4	0.8	0.7
1.1/2"	91	48	24	160	68.3	8.7	6.4	1.5	1.1
2"	108	60	27	160	82.6	11.9	7.9	2.2	1.6
2.1/2"	127	73	29	160	-	-	-	3.1	2.2
3"	146	89	31	160	123.8	11.9	7.9	4.3	2.8
4"	175	114	34	170	-	-	-	6.7	4.8
6"	241	168	41	180	211.1	11.9	7.9	15	7.8
8"	302	219	47	180	269.9	11.9	7.9	28	14
10"	356	273	53	185	323.9	11.9	7.9	43	19
12"	413	324	59	185	381	11.9	7.9	64	26
14"	457	356	63	190	419.1	11.9	7.9	83	34
16"	508	406	68	190	469.9	11.9	7.9	110	41
18"	575	457	75	200	533.4	11.9	7.9	155	58
20"	635	508	84	200	584.2	13.5	9.5	211	77
24"	749	610	99	210	692.2	16.7	11.1	344	117

Class 900 RTJ

Diameter (inches)	A	B	C	K	E	F	G	Unit weight spade Kg	Unit weight spacer Kg
1/2"	61	19	23	170	39.7	8.7	6.4	0.8	0.7
3/4"	67	25	24	170	44.5	8.7	6.4	0.9	0.8
1"	72	32	25	170	50.8	8.7	6.4	1.1	0.9
1.1/2"	92	48	27	170	68.3	8.7	6.4	1.7	1.3
2"	124	60	34	170	95.3	11.9	7.9	3.5	2.7
2.1/2"	137	73	32	170	-	-	-	4.0	2.9
3"	156	89	34	170	123.8	11.9	7.9	5.4	3.7
4"	181	114	38	170	-	-	-	7.9	4.9
6"	241	168	46	180	211.1	11.9	7.9	18	9.6
8"	308	219	54	190	269.9	11.9	7.9	33	17
10"	362	273	61	190	323.9	11.9	7.9	51	23
12"	419	324	68	190	381	11.9	7.9	75	31
14"	467	356	80	200	419.1	16.7	11.1	109	47
16"	524	406	86	200	469.9	16.7	11.1	147	60
18"	594	457	98	210	533.4	19.8	12.7	215	89
20"	648	508	105	210	584.2	19.8	12.7	274	107
24"	711	610	125	235	692.2	27	16.9	461	175

Class 1500 RTJ

Diameter (inches)	A	B	C	K	E	F	G	Unit weight spade Kg	Unit weight spacer Kg
1/2"	61	19	23	170	39.7	8.7	6.4	0.8	0.7
3/4"	67	25	24	170	44.5	8.7	6.4	0.9	0.8
1"	72	32	25	170	50.8	8.7	6.4	1.1	0.9
1.1/2"	92	48	27	170	68.3	8.7	6.4	1.7	1.3
2"	124	60	34	170	95.3	11.9	7.9	3.5	2.7
2.1/2"	137	73	36	170	-	-	-	4.4	3.3
3"	168	89	41	180	136.5	11.9	7.9	7.4	5.4
4"	194	114	49	190	161.9	11.9	7.9	12	7.8
6"	248	168	57	190	211.1	13.5	9.5	23	13
8"	318	219	70	200	269.9	16.7	11.1	45	25
10"	371	273	80	210	323.9	16.7	11.1	70	33
12"	438	324	96	210	381	23	14.3	115	53
14"	489	356	105	220	419.1	27	15.9	157	75
16"	546	406	117	220	469.9	30.2	17.5	217	98
18"	613	457	128	235	533.4	30.2	17.5	299	134
20"	673	508	137	250	584.2	33.3	17.5	385	167
24"	794	610	161	270	692.2	36.5	20.6	629	268

Class 2500 RTJ

Diameter (inches)	A	B	C	K	E	F	G	Unit weight spade Kg	Unit weight spacer Kg
1/2"	65	19	24	110	42.9	8.7	6.4	0.7	0.6
3/4"	73	25	26	110	50.8	8.7	6.4	0.9	0.8
1"	83	32	28	110	60.3	8.7	6.4	1.3	1.1
1.1/2"	115	48	36	120	82.6	11.9	7.9	3.0	2.4
2"	134	60	44	120	101.6	11.9	7.9	4.7	3.7
2.1/2"	-	-	-	-	-	-	-	-	-
3"	169	89	52	160	127	13.5	9.5	9.3	6.8
4"	203	114	62	160	157.2	16.7	11.1	16	11
6"	280	168	84	190	228.6	19.8	12.7	40	25
8"	340	219	100	190	279.4	23	0.6	70	40
10"	426	273	124	210	342.9	30.2	17.5	134	77
12"	496	324	140	210	406.4	33.3	17.5	284	114
14"	-	-	-	-	-	-	-	-	-
16"	-	-	-	-	-	-	-	-	-
18"	-	-	-	-	-	-	-	-	-
20"	-	-	-	-	-	-	-	-	-
24"	-	-	-	-	-	-	-	-	-

NOT FORECAST BY STANDARD

Notes:

- 1) All weights are estimated.
- 2) Dimensions are in mm.
- 3) Spectacle blinds may be fabricated either in one piece or two pieces joined by weld.
- 4) Dimensions of RTJ groove to be in accordance with **ANSI B16.5**

